



KETTLITZ-Antitack BTO-48 VC

- technical leaflet -

Antitack BTO-48 VC is a powdered antitack agent, basically containing inert minerals in combination with detergents, anti-foam and anti-rust agents for the treatment of unvulcanized rubber compounds, endless strips and granules. The product itself is most suitable for batch-off machines with spraying and dipping systems.

The antitack film which remains on the surface is fast drying and is easy to control visually.

Antitack BTO-48 VC has been developed according to the most recent economical and ecological requirements. The product itself is supplied as powder concentrate which guarantees superior efficiency.

The powder can be dispersed into water in very short time, also at lower temperatures. The antitack dispersion remains stable, even after a longer period of time. The contamination of the equipment by Antitack BTO-48 VC is very small, considering the high content of pigments.

Physical Properties

Chemical Characteristics		combination of minerals with detergents and antifoam agents
Appearance		beige powder
Ash Content (5 g/1 h/950 °C)	(%)	52.5 ± 2.5
pH Value at 20 °C (diluted 1 : 30)		10 ± 0.5
Physiol. Behavior		see safety data sheet
Storage Stability		2 years under suitable storage conditions
Packing		paper bags containing 15 kg net

Recommendation for use

Depending on the softness/stickiness of the compounds, we recommend a dilution ratio with water of 1 : 30 up to approx. 1 : 50.